



2,000 GALLON WATER TANK

AVAILABLE ON A VARIETY OF CHASSIS BRANDS & MODELS



SPECS

CAPACITY: 2,000 US GALLONS
DIMENSIONS: 98" LONG X 96" WIDE X 64.75" TALL
TANK SHELL: A36 STEEL
TANK ENDS: A36 STEEL, DOMED WITH FLANGE
TEAR PAD: A36 STEEL
TANK BAFFLES: (1) A36 STEEL W/ 20" CRAWL HOLE
TANK RUNNERS: A36 STEEL, FORMED ANGLE
STYLE, FULL LENGTH
TANK SHAPE: MODIFIED ELLIPSE, LARGE RADIUS CORNERS
MAN-WAY: 24" ROUND MAN-WAY, MESH
LIFT OUT GRATE, NO LID
FILL PIPE: 2-1/2" PIPE, BALL VALVE, AND
CAM GROOVE COUPLER
LADDER: REAR MOUNTED, PIPE CONSTRUCTION,
ANTI-SLIP RUNGS FENDERS: A36 STEEL, SPRAY
LINED FINISH, BLACK ONLY, TROUGH STYLE TRAY
MEDIA BLAST SURFACE, PRIMER, AND TOP COAT TANK WHITE
(ADDITIONAL COLORS AVAILABLE AT AN UP-CHARGE),
TANK INTERIOR COATED (STANDARD)
WATER PUMP
4X3 SHAFT DRIVEN WATER PUMP
PTO
INCLUDES REQUIRED FITTINGS FOR CHASSIS
WITH AIR BRAKES
FRONT SPRAY SYSTEM
(2) INDEPENDENTLY OPERATED AIR SPRAY VALVES
MID SPRAY SYSTEM
(1) INDEPENDENTLY OPERATED AIR SPRAY VALVE
LOCATED DRIVER SIDE (PASSENGER SIDE OPTIONAL)
REAR SPRAY SYSTEM
(2) INDEPENDENTLY OPERATED AIR SPRAY VALVES
ON-ROAD WATER TANK PARTS
TIE DOWN HARDWARE AND MISC PARTS
HOSE REEL ASSEMBLY
1-1/2" X 50' MANUAL HOSE REEL MOUNTED AT
REAR OF TRUCK, WITH 50' HOSE AND ADJUSTABLE NOZLE
ELECTRICAL AND LIGHTING
DOT/ICC COMPLIANT LIGHTS & REFLECTORS
TRUCK-LITE WIRING HARNESS
2-1/2" X 50' WATER TRUCK HYDRANT HOSE
3" SUCTION HOSE KIT CONTAINS :
(2) 3" X 10' MXF CAM & GROOVE
(1) 3" X 10' FEMALE CAM & GROOVE X 3" SUCTION STRAINER



833 - 9 - LK - SPEC
www.loadkingtrailers.com

LOAD KINGTM
BY CUSTOM TRUCK (1) SOURCE

*Load King reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.