



PREMIER FIBERGLASS ROOFING CONVEYOR

AVAILABLE FROM 31-43'



SPECS

HEAD SECTION :
ALL ALUMINUM CONSTRUCTION W/ 1/4" BELT LAGGING
FOUR BOLT PILLOW STYLE BEARING HOLDERS
STAINLESS STEEL SUPPORT PLATES & HINGED COVER
EMERGENCY STOP

TAIL SECTION :
ALL STAINLESS STEEL CONSTRUCTED GUARDS,
UTILIZES A STEEL V-GUIDED BELT PULLY

OPTION :
ALUMINUM & STEEL COMBO OR ALL STEEL -
24' - 28' OVERALL BED SPACE

CRADLE :
17" STEEL 1-PIECE HEAVY DUTY CONSTRUCTION,
SUPPORTS CONVEYOR OR FRAME STRUCTURE

BELT :
PVC NON-CONDUCTIVE BELTING
STAINLESS STEEL PADDLES
BELT SPEED = 60' A MINUTE

CROSS SUPPORTS :
STAINLESS STEEL CONSTRUCTION -
RUBBER - COATED RETURN IDLER WHEELS EQUIPPED W/ BEARINGS
HYDRAULIC HOSE ROUTING THROUGHOUT FRAME STRUCTURE IS
CAPTIVE IN HOLDERS
ALL STAINLESS STEEL HARDWARE, BOLTS, NUTS, ETC. HYDRAULIC
STABILIZERS

360° ROTATION ERGONOMIC CONTROLS

ROTATIONAL GEAR BOX IS FIXED FOR LONGER HOSE LIFE

10' INTEGRATED SUB-BASE & MOUNTING DECK DESIGNED TO CARRY
OPTIONAL FORKLIFT KIT

MAST CLEARANCE UP TO 70" BELT LOADED HEIGHT 18" +

FLUSH MOUNTED ROTATION COVER FOR EASIER
ACCESS TO ROTATION SYSTEM, NO STEEL PLATE TO TRIP OVER



833 - 9 - LK - SPEC
www.loadkingtrailers.com

LOAD KINGTM
BY CUSTOM TRUCK (1) SOURCE

*Load King reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.