



SPECS

DIMENSIONS:

20 CUBIC YARDS STRUCK CAPACITY
60,000 LBS RATED NET PAYLOAD
15,400 LBS ESTIMATED BASE TRAILER WEIGHT
40 FOOT OVERALL LENGTH, 102 INCH OVERALL WIDTH 105 INCH OVERALL HEIGHT
64 INCH X 106 INCH HOPPER DUMP OPENING 90" X 187" UPPER HOPPER OPENING
48 INCH 5TH WHEEL HEIGHT

FRAME:

100,000/80,000 STEEL CONSTRUCTION
BOXED TOP RAIL TO PREVENT MATERIAL BUILD-UP GATE END TUBULAR LANDING LEGS REPLACEABLE GATE PIVOT BEARINGS
MULTIPLE POSITIONS FLEXI-SET GATE LIMITER
8 INCH DIAMETER GATE CYLINDER WITH CHROMED
TUBE AND ROD
12V SOLENOID OPERATED GATE CONTROLS ACCESS CENTER FOR GATE AIR COMPONENTS HOLES IN GATE ENDS FOR CHAIN STOPS
RUBBER ANTI-SPRAY / ANTI-SAIL-MUD FLAPS
WITH CENTER COVER
CORNER CASTINGS AT LOWER HOPPER CORNERS

SUBFRAME:

6 SPRING SUSPENSION WITH HEAVY DUTY MULTI- LEAF SPRINGS
49 INCH AXLE SPACING
WINDROW DEFLECTOR ON FRONT AXLE
THREE 22,500 LB AXLE CAPACITY
TWELVE 11 R 22.5 TIRES
12 OUTBOARD MOUNT HUB PILOTED BUDD TYPE
DISC WHEELS
TIMKEN TAPERED ROLLER WHEEL BEARINGS STEMCO WHEEL SEALS WITH GRIT GUARD
RUBBER BUSHED SIDE OSCILLATING 5TH WHEEL OIL SEALS
16 ½ INCH X 7 INCH SPRING BRAKE WITH ABS SYSTEM EXTERNAL AIR DRAIN

OTHER:

DOT RUBBER MOUNTED SEALED BEAM LIGHTS WITH
MODULAR HARNESS
TEREX LOAD KING MUD FLAPS
SHOT BLAST – PRIMED AND PAINTED LOAD KING YELLOW POLY HAND OPERATED AIR VALVE
SWITCH AND WIRING FOR IN CAB CONTROL



833-955-7732
www.loadkingmfg.com



*Load King reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.