



# SPECS

GENERAL DESCRIPTION: 50,000 LB. FIXED-NECK LOWBOY TRAILER WITH BEAVERTAIL & RAMPS.

LOAD CAPACITY: 50,000 LBS. AT 55 M.P.H. (G.V.W.R. 61,000 LBS.)

OVERALL LENGTH: 38'-2"

DECK LENGTH: 18'-0" (FROM GOOSENECK RISER TO 1ST WHEEL WELL)

DECK WIDTH: 8'-6"

DECK HEIGHT: 32-1/2" UNLOADED

FRAME CONSTRUCTION: PIERCED MAINBEAM CONSTRUCTION WITH ONE PIECE INTERLOCKING CROSSMEMBERS.

MAINBEAMS: W16" X 31 LBS. PER FT., GRADE 50 HI-TENSILE.

CROSSMEMBERS: W10" I-BEAM X 12 LBS PER FT., GRADE 50 HI-TENSILE ON 30" CENTERS.

SIDERAILS: C12" X 20.7 LBS. PER FT. GRADE 50 HI-TENSILE.

DECKING: 2" NOMINAL OAK SECURED TO CROSS-MEMBERS WITH 5/16" TORQUE SCREWS.

LANDING GEAR: 4 POSITION, TUBULAR PIN DROP LEGS WITH SAND SHOES

SUSPENSION: HUTCH 9700 MULTI-POINT SPRING WITH RADIUS ROD AXLE TRACKING ADJUSTMENT, 44,000 LB. CAPACITY

AXLES: (2) 22,500 LB. CAPACITY WITH OIL BATH HUBS.

BRAKES: 12-1/4" X 7-1/2" AIR WITH "WABCO" ANTI-LOCK BRAKING SYSTEM AND SPRING PARKING BRAKES.

WHEELS: 8 HOLE, HUB PILOTED DISC

TIRES: (8) 215/75R17.5, (H)

RAMPS: 60" X 22" SPRING ASSISTED.

HITCH: 2" SAE KING PIN.

TIE DOWNS: (8) HEAVY DUTY D-RINGS, 4 PER SIDE.

LIGHTS: 12 VOLT DOT & ICC APPROVED. ALL LIGHTS ARE LED TYPE AND FLUSH

MOUNTED IN RUBBER GROMMETS. WIRING IS RUN IN FLEXIBLE NEOPRENE JACKET AND MODULAR IN DESIGN. 7 WAY PLUG.



833-955-7732  
[www.loadkingmfg.com](http://www.loadkingmfg.com)

**LOAD KING**  
BY CUSTOM TRUCK (1) SOURCE

\*Load King reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.