

LOAD KING 503-4 DFPR RAIL TRAILER

DROP DECK HYDRAULIC FOLDING GOOSENECK



SPECS

50 TON CAPACITY IN 10 FOOT LOAD CONCENTRATION AT 60 MILES PER HOUR 100,000/80,000 PSI YIELD STRENGTH STEEL CONSTRUCTION

CROSSMEMBERS DESIGNED FOR CENTER LOADING IN GOOSENECK, GOOSENECK DROP, AND DECK 14 LASHING RINGS 12 FULL DEPTH SWING OUT OUTRIGGERS PER SIDE FOR 2 INCH BOARDS

¾ HEIGHT REAR BOLSTER EXCAVATOR CUTOUT BOTTOM, PLATED FIRST 4 FEET, WITH

SUBFRAME:
AIR RIDE SUSPENSION WITH AUTOMATIC AND ADJUSTABLE HEIGHT CONTROL

THREE 25,000 LB AXLES

TWELVE (12) 255/70 R 22.5 TIRES

TWELVE (12) B.25 X 22.5 HUB PILOTED BUDD TYPE DISC WHEELS

OIL SEALS

16 ½ INCH X 7 INCH SPRING BRAKES ON 2 AXLES

AUTO SLACK ADJUSTERS

54 ½ AXLE SPACING

REINFORCED FOR OPTIONAL 4TH AXLE CONNECTIONS

PROVIDED (CLOSE COUPLED ONLY)

GOOSENECK:

LOW PROFILE SCRAPER STYLE WITH PARALLEL LINKS

13 HP SELF-CONTAINED HONDA ENGINE

HYDRAULIC PRESSURE TO KINGPIN LOAD CHART
LINKAGE GOOSENECK LOCK PINS LOCATED ON BOTH SIDES OF TRAILER

7 DEGREE APPROXIMATE GOOSENECK LOADING ANGLE 6 INCH DOUBLE TAPERED NOSE PIECE WITH LIFT EYE

TOOL WELL LOCATED OVER KINGPIN AREA FOR STORAGE

GOOSENECK CONTROLS LOCATED AT REAR OF GOOSENECK FOR EASY ACCESS

ADDITIONAL FEATURES:

RAIL CONFIGURATION INCLUDES SET OF RAMPS AND RAIL

MID-TURN SIGNAL AND CLEARANCE LIGHT

DOT RUBBER MOUNTED SEALED BEAM LIGHTS WITH MODULAR HARNESS

MUD FLAPS

RED AND WHITE CONSPICUITY STRIPING

SHOT BLAST - PRIMED AND PAINTED BLACK POLYURETHANE







833-955-7732 www.loadkingmfg.com



^{*}Load King reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.