

LOAD KING 503-705-DD-MB DETACHABLE GOOSENECK TRAILER DROP DECK USED WITH A MECHANICAL BOOSTED

DROP DECK, USED WITH A MECHANICAL BOOSTER



SPECS

DIMENSIONS: 70 TON CAPACITY IN 12 FOOT LOAD CONCENTRATION AT 60 MPH 100,000/80,000 PSI YIELD STRENGTH STEEL CONSTRUCTION 35,500LB ESTIMATED BASE WEIGHT

26 FOOT DECK LENGTH, 9 FT WIDE 26 INCH LOADED DECK HEIGHT 8 INCH LOADED GROUND CLEARANCE 36 INCH FRONT FLIP UP RAMPS

51 INCH 5TH WHEEL HEIGHT

HEAVY DUTY I-BEAM CROSSMEMBERS
2 LASH RINGS ON REAR BRIDGE AND 2 ON TOP OF NECK
7 LASHING BARS EACH SIDE OF DECK INSIDE HOLES
13 FULL DEPTH SWING OUT OUTRIGGERS PER SIDE

2 INCH APITONG OUTER WITH OPEN CENTER AND

FLAG POCKETS FRONT OF DECK AND REAR OF TRAILER
30 DEGREE RADIUS REAR DROP
34 HEIGHT REAR BOLSTER
EXCAVATOR CUTOUT BOTTOM PLATED TO FIRST AXLE

SUBFRAME:

THREE 25,000 LB AXLES
54 ½" INCH AXLE SPACING
AIR LIFT 3RD AXLE WITH SCALE-0-MATIC

TWELVE (12) 8.25 X 22.5 HUB PILOTED STEEL DISC WHEELS

AUTO SLACK ADJUSTERS
INNER SUBFRAME SUSPENSION BEAMS AND CONNECTIONS FOR
OPTIONAL 2 AXLE MECHANICAL BOOSTER
NOTE: 3RD AXLE MOUNTED DIRECTLY TO TRAILER MAIN FRAME

NON-GROUND BEARING GOOSENECK DESIGN

WET KIT OPERATION, LESS TRACTOR PORTION
HYDRAULIC SELF-LIFTING DETACHABLE GOOSENECK,
ABLE TO LIFT ABOVE OR BELOW TRANSPORT POSITION
HYDRAULIC FRAME LIFT SUPPORT

HYDRAULIC PRESSURE TO KINGPIN LOAD CHART

AIR-ACTIVATED, SELF-LOCKING PIN ON GOOSENECK, POSITIVE LOCK

ADDITIONAL EQUIPMENT: MID-TURN SIGNAL AND CLEARANCE LIGHT DOT RUBBER MOUNTED SEALED BEAM LIGHTS WITH MODULAR HARNESS

MUD FLAPS

RED AND WHITE CONSPICUITY STRIPING

COMPATIBILITY: HELPER DOLLY: HD 702GMECHANICAL BOOSTER: MB502







833-955-7732 www.loadkingmfg.com



^{*}Load King reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.