



Load King Stinger 19-51TM

19Ton Boom

New Peterbilt 567

CRANE SPECIFICATIONS

Engine

X15 565Hp
3 Paccar Batteries
37.4 CFM Air Compressor
Intebrake

Transmission

Eaton RTLO18918B 18-Speed

Front Axle

Dana Spicer D2000F 20,000LB, 3.5" Drop
Tires: 425/65R22.5
Aluminum Wheels

Front Suspension

Taper Leaf Springs, Shocks 20,000Lb

Rear Axle

Dana Spicer D46-172 46,000 Lb
DIFF Lock Tandem Axles
Ratio 4.10
Tires: 11R24.5
Aluminum Wheels

Rear Suspension

Hendrickson HMX460 46,000 Lbs
54" Axle Spacing

Fuel Tanks

120 Gallon Aluminum Fuel Tank- LH
DEF Tank Small-RH

Cab Features

VOC 121 BBC Aluminum Cab & Metton Hood
Cab Air Suspension
Premier Interior - Sterling Gray
Peterbilt Keyless Entry
High Back Air Ride Mordura Driver Seat
RH & LH Driver Seat Arm Rests
High Back Non Adjustable Mordura Passenger Seat
LH Passenger Arm Rest Only
Adjustable Steering Column
Day Cab Rear Window
Power Door Locks And Power Window Lifts
Peterbilt Aero Rear View Mirror
(2) PB Air Horns Round, 23" Length
Roof Mounted Round Horn Shield
Cobra 29 CB Radio MTD Center Of Header
With Weatherband
(5) Marker Lights Aero LED

Fifth Wheel

Holland Fw35 Fifth Wheel Top Plate
Holland Heavy Duty 36" Air Slide
6.6"-7" Fifth Wheel Height
LH Fifth Wheel Release

Load King 19-51TM 19 Ton Boom

19 Tons Capacity Rating
Mainframe Consists Of All-Steel Box Construction
Dual Side Stand Up Controls With Foot Throttle Pedal
Rotation Planetary Gearbox Hydraulic Motor Driven With 370-Degrees
Of Non-Continuous Swing Rotation
Crane Consoles Include 4 Lever Crane Function Control Handles
4 Lever Outrigger Control Handles
Warning Light For High Hydraulic Oil Temperature
51' Three Section Keel Designed Boom Full Power, Mechanically Synchronized
Standard Two-Speed Planetary Hoist - Hydraulic Motor Driven - Maximum
Line Pull 11,100Lbs / 5,532lbs @ Low Speed/High Speed Combined Flow Switch
Rated Capacity Limiter System With Digital Read Out Display, And Integrated
Work Area Definition Program
Tractor Mount Sub-Base With Boom Rest Positioned Behind Cab For Forward
Stow Boom Configuration
Single Front Bumper Outrigger (360Degree Capacity)
240 x 9/16 Rotation Resistant Cable
Load Ball With Non-Swivel Hook
1- Sheave (17.5 Ton) Load Block

Optional

18'-29' (2-Piece) Jib Add: \$13,500

855-399-5991 -- www.loadkingmfg.com

DISCLAIMER: Specifications are believed to be correct, but may contain errors and/or omissions.
Pictures are representative and may not be identical.

- PRICE: \$265,900
- FET Included
- Ex Works: Kansas City, MO

QUOTE NUMBER: HC1.11-D_19

EXPIRATION DATE: 6-30-19