

Load King Stinger 35-100RS 35Ton Boom New Peterbilt 348

CRANE SPECIFICATIONS

Engine

Paccar PX-9 350Hp 2 Paccar Batteries 18.7 CFM Air Compressor VGT Exhaust Brake

Transmission

Eaton RTO14908LL 10-Speed

Front Axle

. . .

. . .

. . .

. . .

Paccar Steer Axle 20,000 LB, 4" Drop Tires: 425/65R22.5 Aluminum Wheels

Front Suspension

Taper Leaf Springs Shocks 20,000 LB

Rear Axle

Dana Spicer D46-172 46,000 Lb DIFF Lock Tandem Axles Ratio 4.10 Tires: 11R22.5 Steel Wheels

Rear Suspension

Hendrickson HMX460 46,000 Lbs 54" Axle Spacing

Fuel Tanks

90 Gallon Aluminum Fuel Tank-LH Small DEF Tank

Cab Features

Aluminum Cab 108" BBC Metton Hood Cabmate Cab Air Suspension Peterbilt Ultraride Passenger Seat Peterbilt Ultraride Driver Seat Drivers Armrests - LH & RH Air Ride Driver Non-Air Ride Passenger High Back Driver Low Back Passenger Mordura Driver Mordura Passenger Adjustable Steering Column - Tilt Only Interior Grey / Black Day Cab Rear Window One-Piece Curved Windshield Stainless Steel Mirrors 7"X16" W/Heat Element (1) Air Horn 24.5" Chrome - Round Includes Polished Horn Shield (5) Marker Lights, Aero Led

Load King 35-100RS 35 Ton Boom

35 Tons Capacity Rating Mainframe Consists Of All-Steel Box Construction Rotating/Seated Controls With Foot Throttle Pedal Rotation Planetary Gearbox - Hydraulic Motor Driven With 360-Degrees Of Continuous Rotation (No Swing Stop) 4 Lever Crane Function Control Handles 4 Lever Outrigger Control Handles Hydraulic Oil Cooler Frame Mounted To Underbody Rated Capacity Limiter System With Digital Read Out Display Integrated Work Area Definition Program Three Section Vane Pump Is PTO Driven And Allows Independent Functioning Of Boom, Winch And Swing Operations Standard Two-Speed Planetary Hoist - Hydraulic Motor Driven Maximum Line Pull 15,000lbs / 6,950Lbs @ Low Speed/High Speed Setting 100' Four Section Keel Designed Boom, Full Power,

Mechanically Synchronized 30.5' - 55' (2 Piece) Jib
Enclosed Operators Cab With Propane Heater
Front Single Bumper Outrigger (360 Degree Capacity) 350' x 5/8" Rotation Resistant Cable
Load Ball With Non-Swivel Hook
2-Sheave (30Ton) Load Block
Air Shift PTO

Options

Basket And Remotes Add \$26,900 Pusher Axle Add \$8,000

855-399-5991 -- www.loadkingmfg.com

• • PRICE: \$357,900

FET Included

Ex Works: Kansas City, MO