



SPECS

- STANDARD PLATFORM CAPACITY OF 350 LBS.
- HEAVY DUTY ALUMINUM INNER BOOM WITH DROP DOWN BOOM TIP.
 - FIXED FLYBOOM.
- ENGINE START/STOP CONTROLS AT PLATFORM AND REMOTE LOWER CONTROLS.
 - NON-CONTINUOUS 370 DEGREE ROTATION WITH ELECTRIC LIMIT SYSTEM.
 - TWO GPM (7.57 LPM) OPEN CENTER HYDRAULIC SYSTEM.
 - HYDRAULIC OIL RESERVOIR WITH 7 GALLON (26.5L) CAPACITY BUILT INTEGRAL TO PEDESTAL.
 - SELF-LOCKING WORM GEAR ROTATION DRIVE WITH SHEAR BALL BEARING.
- BOOM ARTICULATION FROM 8 DEGREES BELOW HORIZONTAL TO 80 DEGREES ABOVE HORIZONTAL.
 - ELECTRIC ROTATION LIMIT SYSTEM.
- VAN MOUNT PEDESTAL AND MOUNTING HARDWARE FOR LOW ROOF TRANSIT VAN INSTALLATION.
 - HAND HELD REMOTE LOWER CONTROLS INCLUDING 30 FT. CABLE AND OVERRIDE.
 - ELECTRIC VARIABLE SPEED CONTROLS AT PLATFORM INCLUDING MASTER CONTROL, EMERGENCY STOP, AND CONTROL COVER.
 - HYDRAULIC POWER SUPPLIED BY ENGINE BELT DRIVE SYSTEM.
- WALK IN HYDRAULIC LEVELLED 24 IN. X 24 IN. X 42 IN. (.61M X .61M X 1.07M) END MOUNTED FIBERGLASS PLATFORM WITH DOOR AND VINYL COVER
 - NON-LUBE BEARINGS USED AT ALL PIVOT POINTS.
 - MULTI-LINK PLASTIC HOSE CARRIER SYSTEM THROUGH BOOMS.
 - 120V WIRING TO PLATFORM WITH GFCI RECEPTACLE.
 - 12 VOLT DC BACKUP PUMP.
 - SAFETY HARNESS AND LANYARD.
 - 2 GPM BELT DRIVE KIT.
 - REAR ALUMINUM BUMPER EXTENSION.
 - UNIT PAINTED STANDARD WHITE URETHANE.
 - TWO OPERATORS AND SERVICE MANUALS.
 - ANSI A92.2 DATA PLATE



888-925-0858
www.customtruck.com

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

